

# Specification

## 1. Item

Product	2390~2500MHz 15W High Power Amplifier
Partnumber	EHM-2390-45-46

## 2. Revision History

Issued / Revision	R&D Approved	Revision Detail



Design	R & D	Approval
		
CYKIM		

Customer:	Date:	Part No.: EHM-2390-45-46
-----------	-------	--------------------------

### General Specification

No.	Parameter	Specification	Unit
1	Operating Frequency Range	2390~2500MHz	-
2	Output Power(Psat)	30	-
3	Gain	48dB typ.	-
4	Gain Flatness	±1.0dB typ.	-
5	Normal Input Power	-3dBm	-
6	Input/output VSWR	1.5	-
7	Harmonics	-45dBc typ.	-
8	Spurious Signal	-60dBc	-
9	Operating Voltage	28V	-
10	Current Draw@45dBm	2.8A max	-
11	Load VSWR	∞ : 1 VSWR	-
12	Protection	Over current : @ ≥ 3.3A Over temperature : Shutdown @ ≥ +90°C, Auto-restart @ +80°C	-

### Mechanical Specification

No.	Parameter	Specification	Unit
1	Dimension	180*115*25	-
2	RF Connector	SMA Female	-
3	DC/Interface Connector	D-SUB 9Pin Male	-
4	Operating Case Temperature	-20 ~ +80°C	-
5	Storage Temperature	-40 ~ +90°C	-
6	Relative Humidity(Non-condensing)	5~95%	-

## Pin Description

Pin No.	Description	Specifications
1	Current Monitor	Analog voltage related to main current
2	NC	
3	Temperature Monitor	$V_o = (10\text{mV}/^\circ\text{C} \times \text{Temp}) + 500\text{mV}$
4	NC	
5	Enable/Disable	Enable: TTL "Low", Disable: TTL "High"(3.3V) (Internally pull down)
6,7	VDD	+28VDC
8,9	GND	Ground

## Mechanical Dimension [Unit: mm]

